

INDFLOC[®] 435

Polyelectrolyte's For Solid-Liquid Separation & Dewatering

Application

INDFLOC 435 is high efficiency polyelectrolyte, specially designed for solid - liquid separation process. Applications include sedimentation, thickening and clarification of suspension; clarification of aqueous liquor by sedimentation; Dewatering of pulp and sludge for the recovery of liquor or disposal of solids by filtration and centrifugation sludge for the recovery of liquor or disposal of solids by filtration Belt Press and centrifugation.

Features

- Marked increase in underflow density.
- Rapid Settling.
- High filtration rate.
- Efficient filter cake washing.
- Effective at low dosages.
- Easy to prepare solution and apply.
- Completely miscible with water.
- Improved filter clarity.
- Increase throughput.

Product Specifications

| | |
|-----------------------------------|----------------------------|
| Appearance | : Crystalline white Powder |
| Ionic character | : Medium Cationic |
| pH of 0.1% solution | : 3.0 – 5.0 |
| Stock Solution 0.1% viscosity cPs | : 25 - 50 |
| Solids | : 88 - 92 |

Directions for use

INDFLOC 435 may be unloaded manually or pumped directly into the dilution tank from the container. Prepare stock solution (1.0 to 1.5%w/v) of the polyelectrolyte using filtered water. Prepare feed solution by diluting the stock solution directly or by on-line using filtered water. For small systems chemicals can be dosed by gravity or by dosing equipment. However, for larger systems use of dosing system is recommended. Our Sales Engineer will recommend the dosing equipment best suited for your requirement.

Limitations and handling

Do not store the material in open. Keep the container tightly closed when not in use. These products exhibit very low order of oral toxicity. No special care is required in handling these products.

Storage

Keep container tightly closed in a cool place.

No warranty, expressed or implied is made, except that the products herein discussed comply with the chemical description. Buyer assumes risks of the use, storage and handling. Ion Exchange (India) Ltd. shall not be liable for any incidental or consequential damages arising directly or indirectly in connection with the purchase, use, storage or handling of this product. The information contained herein is, to the best of our knowledge is true and accurate. However, all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. We disclaim any liability incurred in connection with the use of these data or suggestions.

INDION, **INDFLOC** and **IONREF** are the registered trademark of Ion Exchange (India) Ltd.



ION EXCHANGE (INDIA) LTD.

Corporate Office

Ion House, Dr. E. Moses Road, Mahalaxmi, Mumbai - 400011 | Tel: +91 22 6231 2000 | E-mail: ieil@ionexchange.co.in

Chemical Division

4th Floor, Riviera Apartment, Dwarkapuri Colony, Punjagutta, Hyderabad 500 082 | Tel: +91 40 6831 3101 | E-mail: hydco@ionexchange.co.in

International Division

R-14, T.T.C MIDC, Thane - Belapur Road, Rabale, Navi Mumbai - 400 701 | Tel: +91 22 6857 2400 | E-mail: export.sales@ionexchange.co.in

Regional and Branch Offices

Bengaluru | Bhubaneswar | Chandigarh | Chennai | Delhi
Hyderabad | Kolkata | Lucknow | Vadodara | Vashi
Visakhapatnam

Overseas Offices

Bahrain | Bangladesh | Canada | Indonesia | Kenya
Malaysia | Oman | Saudi Arabia | Singapore | South Africa
Sri Lanka | Tanzania | Thailand | UAE | USA

Manufacturing Units

India - Ankleshwar | Hosur | Patancheru | Rabale | Verna | Wada

Overseas - Bangladesh | Indonesia | Saudi Arabia | UAE

All India Service and Dealer Network

www.ionexchangeglobal.com

